

# DUAL SH DBC Low Profile SST w/ LWR FCT

Height: 32.1" Width: 18.0" Depth: 25.4"  
(81.5cm) (45.7cm) (64.5cm)



- Brews either 1/2 gallon or 1 gallon (1.9 or 3.8L) batches
- Brews up to 19.3gallons (73.1L) of perfect coffee per hour
- No hot surfaces in coffee holding area
- Reduce accidents with safety features that decrease hot splashes from funnel, eliminate brewing when funnel or server is not present
- Patented server heat control automatically shuts off once target temperature is reached (Can be set to 175°-190°F (79.4°-87.8°C))
- Simplify installation and calibration by creating your own recipe cards and dedicated funnels with the BrewWISE Recipe Writer using your PC (Windows® compatible).
- SplashGard® funnels deflect hot liquids away from the hand
- Energy saver mode reduces tank temperature during idle periods
- Operate any combination of BrewWISE equipment error-free with wireless brewer-grinder interface through Smart Funnel with SplashGard®
- Stores individual coffee and flavor profiles using adjustable water volume, bypass percentage, pulse brew, and pre-infusion timing
- Troubleshoot all switches and electrical components from the front panel with advanced diagnostic service tools
- Servers not included unless otherwise noted

Server(s) sold separately

Agency:



## Specifications

**Product #:** 33500.0046

**Water Access:** Plumbed

**Finish:** Stainless

**Interface:** Wireless

**Funnel:** Black Plastic

**Faucet:** Lower

## Additional Features

Low Profile

BrewWISE

## Electrical & Capacity

Volts*	Amps	Watts	Cord Attached	Plug Type	8oz cups/hr 236ml cups/hr	Input H <sub>2</sub> O Temp.	Phase	# Wires plus Ground	Hertz
120/208-240	23.9-29.1	4980-6800	No	-	-	60°F (15.5°C)	1	3	60

\*When a BUNN is machine rated 120/208-240V, 120/208V or 120/240V, the higher voltage is the supply voltage needed to power the machine. The 120V is there to supply power to some components rated 120V in the machine, but it is not the supply voltage and would not power the machine if the machine is marked with the before mentioned ratings.

## Plumbing Requirements

PSI	kPa	Fitting Supplied	Water Flow Required (GPM)
20-90	138-621	1/4" Male Flare Fitting	-

## CAD Drawings

2D	Revit	KLC
●		



BUNN® reserves the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment. For most current specifications and other info visit [bunn.com](http://bunn.com).

Last Updated:  
09/04/2020

Unit			Shipping					
	Height	Width	Depth	Height	Width	Depth	Weight	Volume
English	32.1 in.	18.0 in.	25.4 in.	35.9 in.	21.6 in.	27.1 in.	99.760 lbs	12.178 ft <sup>3</sup>
Metric	81.5 cm	45.7 cm	64.5 cm	91.1 cm	54.9 cm	68.9 cm	45.251 kgs	0.345 m <sup>3</sup>



BUNN® reserves the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment. For most current specifications and other info visit [bunn.com](http://bunn.com).


Last Updated:  
09/04/2020

# Related Products & Accessories: DUAL SH DBC Low Profile SST w/ LWR FCT (33500.0046)



FILTERS, GOURMET 500  
500/1 50/CL

Product #: 20138.1000



DRIP TRAY KIT, DUAL &  
SH

Product #: 27150.0000



1SH STAND, 120V

Product #: 27825.0000



1SH STAND, 120V BLK

Product #: 27825.0003



2SH STAND, 120V

Product #: 27875.0000



2SH STAND, 120V BLK

Product #: 27875.0003

CARD ASSY, RECIPE  
TRANSFER (BRW)

Product #: 34447.0016



BUNN® reserves the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment. For most current specifications and other info visit [bunn.com](http://bunn.com).

Last Updated:  
09/04/2020

# Serving & Holding Options: DUAL SH DBC Low Profile SST w/ LWR FCT(33500.0046)



SH-S SERVER 1G 60  
MIN ADJ TMR

Product #:27850.0046



BUNN® reserves the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment. For most current specifications and other info visit [bunn.com](http://bunn.com).

Last Updated:  
09/04/2020