

iMIX®-5S+ Top Hinge

Height: 32.8" Width: 19.3" Depth: 24.0"
(83.3cm) (49.0cm) (61.0cm)



- 7gal (26.5L) hot water tank to meet peak serving times
- Alphanumeric display allows adjustments and service operational testing from front of machine. Also communicates advertising messages, machine status and technical support contact information
- Can be set as push and hold or single size portion control
- Capacity: Five 8lb (3.6kg) hoppers
- Cup clearance at 7.25" (18.4cm) to accommodate popular cup sizes [adjustable to 8.12" (20.6cm)]
- Easily removable side panels for complete access to service components
- Front of machine access to tank drain, dump valves, auger and whipper motors and control board for easy service set up and calibration
- High speed heavy-duty whipper for complete product mixing
- High efficiency LED lighted front graphics for merchandising
- Spring-loaded, all metal auger drive system for easy hopper installation
- Variable speed motors allow control of product consistency in mixing chamber (.75 to 6.6 grams of powder per second)

Agency:



Specifications

Product #: 38100.0050

Water Access: Plumbed

Finish: Black

Hoppers: Five

Door: Lit

Door: Top Hinge

Dispense: Portion Control

Dispense: Push Button

Additional Features

Electrical & Capacity

Volts*	Amps	Watts	Cord Attached	Plug Type	8oz cups/hr 236ml cups/hr	Input H ₂ O Temp.	Phase	# Wires plus Ground	Hertz
120	15	1800	Yes	NEMA 5-15P	72	60°F (15.5°C)	1	2	50/60

*When a BUNN is machine rated 120/208-240V, 120/208V or 120/240V, the higher voltage is the supply voltage needed to power the machine. The 120V is there to supply power to some components rated 120V in the machine, but it is not the supply voltage and would not power the machine if the machine is marked with the before mentioned ratings.

Plumbing Requirements

PSI	kPa	Fitting Supplied	Water Flow Required (GPM)
20-100	138-689	1/4" Male Flare Fitting	-

WARNING:


CAD Drawings

2D	Revit	KLC
●	●	●



BUNN® reserves the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment. For most current specifications and other info visit bunn.com.

Last Updated:
07/08/2025



Unit			Shipping					
	Height	Width	Depth	Height	Width	Depth	Weight	Volume
English	32.8 in.	19.3 in.	24.0 in.	40.4 in.	23.2 in.	28.9 in.	136.000 lbs	15.676 ft³
Metric	83.3 cm	49.0 cm	61.0 cm	102.6 cm	58.9 cm	73.4 cm	61.690 kgs	0.444 m³









BUNN® reserves the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment. For most current specifications and other info visit bunn.com.

Last Updated:
07/08/2025

Related Products & Accessories:iMIX®-5S+ Top Hinge(38100.0050)

 DISPLAY, GRAPHICS (iMIX-4/5) <hr/> Product #: 36768.0000	 DISPLAY, GRAPHICS ICED CAP <hr/> Product #: 36768.0005	 WATER FILTER, EQHP-10L <hr/> Product #: 39000.0001 ³	 WATER FILTER, EQHP-10 <hr/> Product #: 39000.0004 ³	 SYSTEM, WQ-55(2)5L <hr/> Product #: 56000.0001 ¹
--	---	--	---	---

 SYSTEM, WQ-55(2)5 <hr/> Product #: 56000.0004 ¹	 SYSTEM, WEQ-10(1.5)5L <hr/> Product #: 56000.0024 ¹	 SYSTEM, WEQ-10(1.5)5 <hr/> Product #: 56000.0027 ¹	 CARTRIDGE, WQ-55(2)5L <hr/> Product #: 56000.0101 ¹	 CARTRIDGE, WQ-55(2)5 <hr/> Product #: 56000.0104 ¹
--	--	---	--	---

 CARTRIDGE, WEQ-10 (1.5)5L <hr/> Product #: 56000.0121 ¹	 CARTRIDGE, WEQ-10 (1.5)5 <hr/> Product #: 56000.0122 ¹
---	--

¹NSF Certified ²NSF Certified with spec sheet model listed ³NSF Certified under Solventum Purification ⁴NSF Certified under Mavea LLC ⁵NSF Certified under Zojirushi ⁶NSF Certified under Qins Inc ⁷NSF COMPONENT Certified



BUNN® reserves the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment. For most current specifications and other info visit bunn.com.

Last Updated:
07/08/2025

Serving & Holding Options: iMIX®-5S+ Top Hinge(38100.0050)

Serving and Holding selections are currently unavailable. Please contact your sales representative to find out more information.

¹NSF Certified ²NSF Certified with spec sheet model listed ³NSF Certified under Solventum Purification ⁴NSF Certified under Mavea LLC ⁵NSF Certified under Zojirushi ⁶NSF Certified under Qins Inc ⁷NSF COMPONENT Certified



BUNN® reserves the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment. For most current specifications and other info visit bunn.com.

Last Updated:
07/08/2025